



















BATTERY TYPE	CCA 0° F -18° C	CAPACITY AH (10HR)	CHARGING TIME IN HOURS		MAXIMUM DIMENSIONS						ASSEMBLY FIGURE	VENT POSITION	WEIGHT WITHOUT ACID		ACID VOLUME (Liter)	TERMINAL	
					MILLIMETERS (±2 mm)			INCHES (±1/16 in)					KG	LBS			
			At 500mA	At 750mA	L	W	H	L	W	H							
490-2001	6N2-2A UNV	10	2	2-4	2-3	70	46	97	2 3/4	1 13/16	3 13/16		A	0.40	0.88	0.15	—
490-2016	6N2A-2C UNV	10	2	2-4	2-3	71	47	105	2 13/16	1 7/8	4 1/8		D	0.40	0.88	0.15	—
490-2021	6N4-2A UNV	10	4	4-8	3-6	71	71	94	2 13/16	2 13/16	3 11/16		B	0.60	1.32	0.24	—
490-2035	6N4B-2A UNV	10	4	4-8	3-6	101	47	95	3 15/16	1 7/8	3 3/4		A	0.70	1.54	0.24	—
490-2034	6N4A-4D	10	4	4-8	3-6	60	60	130	2 3/8	2 3/8	5 1/8		A	0.70	1.54	0.24	—
490-2042	6N4C-1B	10	4	4-8	3-6	69	70	104	2 11/16	2 3/4	4 1/16		B	0.60	1.32	0.24	—
490-2045	6N5.5-1D	10	5.5	6-11	4-8	88	70	98	3 7/16	2 3/4	3 7/8		C	0.80	1.76	0.24	—
490-2046	6N5.5-1D-1	10	5.5	6-11	4-8	88	70	98	3 7/16	2 3/4	3 7/8		C	0.80	1.76	0.24	—
490-2050	6N6-1B	10	6	6-12	4-8	99	56	109	3 7/8	2 3/16	4 1/4		E	0.80	1.76	0.24	—
490-2053	6N6-3B	10	6	6-12	4-8	99	58	109	3 7/8	2 1/4	4 1/4		E	0.80	1.76	0.24	E
490-2054	6N6-3B-1	10	6	6-12	4-8	99	58	109	3 7/8	2 1/4	4 1/4		B	0.80	1.76	0.24	E
490-2057	6N6-1D-2	10	6	6-12	4-8	99	56	109	3 7/8	2 3/16	4 1/4		C	0.80	1.76	0.24	—
490-2075	B39-6	20	7	7-14	5-10	125	48	125	4 15/16	1 7/8	4 15/16		-	0.90	1.98	0.28	E
490-2077	B49-6	30	10	10-20	7-14	90	83	161	3 9/16	3 1/4	6 5/16		-	1.40	3.08	0.42	E
490-2060	6N11-2D	30	11	11-22	8-15	148	69	103	5 13/16	2 11/16	4 1/16		C	1.50	3.30	0.42	E
490-2062	6N11A-1B	30	11	11-22	8-15	120	60	131	4 11/16	2 3/8	5 1/8		B	1.60	3.52	0.57	E
490-2065	6N12A-2C	30	12	12-24	8-16	154	55	115	6 1/16	2 3/16	4 1/2		D	1.77	3.90	0.42	E
490-2067	6N12A-2D	30	12	12-24	8-16	154	55	115	6 1/16	2 3/16	4 1/2		C	1.77	3.90	0.42	E